

DEALER

ORDER N°

SERIAL N°

EXPECTED DELIVERY TIME

Specific configuration

Table version

FRAME SIZE SX-ST8D SX-ST10 SX-ST12

SIDE COMPACT WITH BATTERY PACK

Master

NOMINAL OUTPUT LEVEL +6dBu +4dBu

MIC POWER ELECTRET PH 48V

COM FULL DUPLEX NORMAL

NO MONITOR ATTENUATION NORMAL

RETURN LEVEL + 8 dB P/A RET = AFL

Back panel XLRs

STANDAR VERSION (MIX 1, 2, 3, 4 OUT / AUX 1, 2, 3, 4)

AMERICAN VERSION (MIX 1, 2, 3, 4 OUT / AUX 1, 2 / RETURN 1, 2)

OTHER.....

Input

NUMBER INPUT MODULE

DIRECT ASSIGNATION (S13) PRE FADER, PRE PAN (1-2) POST FADER, PRE PAN (2-3)

LINE OUT (S4) PRE EQ PRE FADER POST FADER

TRIM POT DETENT YES NO

LOW CUT FILTER (S7) ALWAYS ON (1-2) DEPENDING TO EQ SWITCH (2-3)

AFL (S12-13) POST PAN (1-2) PRE PAN (2-3)

POWER UP ON/OFF STATUS (S8) ON (ASS) OFF (NA)

ON / OFF LED (S9) LIGHT WHEN ON (NA) LIGHT WHEN OFF (ASS)

DELAY ON SWITCH ACTIVATION NO DELAY 125 ms 250 ms (France : 250 ms)

A/D converter, Recorder A/D A/D PREWIRED NO PRE-WIRING

RECORDER REC PREWIRED NO PRE-WIRING

HARD DISC NUMBER

CALIBRATION 0 dBvu = -9 dBFS EBU (+ 6dBu OUT REFERENCE / IN ADC = 0dBu)

0 dBvu = -18 dBFS EBU (+ 6dBu OUT REFERENCE / IN ADC = 0dBu)