

SONOSAX SX-ES64

PURCHASE ORDER FORM

Distributor / Dealer:

P.O. nr:

Date of order:

Customer, end user:

Serial Nr:

Expected delivery date:

Communications / Notes:

- Standard Version no option
- Option RF Filters
- Option 3 bands EQ number of Equalizer modules:.....
- Option A/D Converter

MIC/LINE INPUT CHANNELS ** denotes standard factory set-up

- CHANNEL ASSIGNMENT : PRE-FADER / PRE-PAN ** POST-FADER / PRE-PAN
- DIRECT OUTPUT (Line Out) : PRE-EQ POST-EQ** POST-FADER
- FEED TO ADC : PRE-EQ POST-EQ** POST-FADER
- PRE-LISTENING "PFL" : PRE-FADER ** (PFL) POST-FADER (AFL)

MASTER & MONITORING ** denotes standard factory set-up

- NOMINAL OUTPUT LEVEL : +6dBu ** +4dBu *Line Level outputs, for 0 reading on peak-meter*
- MIC COM/SLATE : INTERNAL ** EXTERNAL
- COM/PL ATTENUATION : ATTENUATION ** NO ATTENUATION *Monitoring attenuation with COM or PL*
- MONITORING RETURN "PFL": PRE-FADER ** (PFL) POST-FADER (AFL)

A/D CONVERTER ** denotes standard factory set-up

- SAMPLING RATE & BIT DEPTH: 48 / 96 kHz at 24 bits **
 192 / 96kHz at 24 bits
 48kHz at 16 bits / 96 kHz at 24 bits
- OUTPUT AES#3: DIRECT OUT CH 5 & 6 ** MASTER 3 & 4

OPTIONAL CONNECTOR

HIROSE 10 Pin
 RM15TRD-10S

TAJIMI 12 Pin
 PRC 05R 12F

OTHER
 Please specify

